

# REMOTE LANE CARRIERS SPECIFICATIONS



**TRANSTRAX® REMOTE LANE CARRIER**



**CAPTIVE CARRIER TRANSTRAX**



**LICENSE PLATE RUNNER TRANSTRAX**

|  |   |  |  |
|--|---|--|--|
| <b>Ratings</b>                                       | UL-listed   | UL-listed  | UL-listed  |
| <b>Materials used</b>                                | Aluminum tube/track;<br>Aluminum & Plastic carrier  | Aluminum tube/track;<br>Aluminum carrier   | Aluminum tube/track;<br>Aluminum & Plastic carrier   |
| <b>Finish options</b>                                | Not available   | Carrier - red powder coat standard   | Carrier - black aluminum and ABS plastic   |
| <b>Unit height (range)</b>                           | 9' 5-3/4" - 16' to top of horizontal tube   | 9' 5-3/4" - 16' to top of horizontal tube  | 9' 5-3/4" - 16' to top of horizontal tube  |
| <b>Unit max extension/horizontal run</b>             | 60 ft. at 16 ft. elevation  | 30 ft. at 16 ft. elevation   | 30 ft. at 16 ft. elevation   |
| <b>Track configurations</b>                          | Standard, Splayed, Reverse Lane   | Standard, Splayed, Reverse Lane  | Standard, Splayed, Reverse Lane  |
| <b>Carrier dimensions / capacity</b>                 | 1-3/8" L x 4-1/4" W x 10" H;<br>1 lb max weight load  | 7-1/2" L x 5-1/4" W x 10-1/2" H;<br>1 lb max weight load   | Plate area = 6-1/4" D x 13-1/4" H x 13/16" W; box = 4-1/8" W x 10" H x 1-1/2" D; 1 lb. max weight load   |
| <b>Required clearances (wall openings, overhang)</b> | 12"x12" horizontal clear channel, 12"x12" wall opening, 12"x12" ceiling opening, 6" rec. counter clearance (vertical) for control box                   | 16" H x 12" W wall opening, 16-3/4" x 16-3/4" opening for ceiling trim, 16" clear channel for horizontal run, 6" rec. counter clearance (vertical) for control box | 16" H x 12" W wall opening, 16-3/4" x 16-3/4" opening for ceiling trim, 16" clear channel for horizontal run, 6" rec. counter clearance (vertical) for control box |
| <b>Power requirements</b>                            | 110V, PH.1, 20 AMP circuit; interior outlet   | 110V, PH.1, 20 AMP Circuit; Interior Outlet  | 110V, PH.1, 20 AMP Circuit; Interior Outlet  |
| <b>Motor</b>   | 90V DC  | 90V DC   | 90V DC   |
| <b>Controls</b>                                      | Teller: Power, Car, Truck, Recall, Audio; Customer: Send, Help  | Teller: Power, Car, Truck, Recall; Customer: Send, Help  | Teller: Power, Car, Truck, Recall; Customer: Send, Help  |
| <b>Product options</b>                               | Exterior TransTrax skin (beige or stainless steel), customer control box button alignment (left or right), video, audio, vehicle detectors, lane lights | Horizontal enclosure, video, audio, vehicle detectors, lane lights   | Horizontal enclosure, video, audio, vehicle detectors, lane lights   |
| <b>Audio included</b>                                | BavSonic duplex audio   | Exterior components (mic, speaker, call button)  | Exterior components (mic, speaker, call button)  |

Some products may be shown with accessories not included with standard offering or pricing.