
TT Mic Plate Manual

E. F. Bavis & Associates, Inc.

201 Grandin Road
Maineville, Ohio 45039
(513) 677-0500

Copyright 2010 E. F. Bavis & Associates, Inc.
All Rights Reserved

Revised 07/27/10
P/N 00752011

**P.N. 04362991 TT Mic Plate Kit
Bill of Materials**

Part Number	Description	Quantity
00752011	TT Mic Plate Manual	1
04363011	TT Mic Mounting Plate	1
97045001	3/8 Mic Nut	1
55555237	9/64 Screw Machine Drill Bit	1
97026004	0.390 x 0.625 Aluminum Washer	1
06926020	3/8 Hole Plug	1
93080123	#8 x 1/2 Phillips Flat	3

Installation Instructions

REFER TO THE DIAGRAM ON THE NEXT PAGE

1. Disconnect the speaker harness and remove the mic from the teller vertical.
2. Position the mic plate 1" up from the teller control and centered left to right.
3. Trace the 3 holes in the mic plate on the vertical tube with a pencil.
4. Drill the center hole (where the mic wire will go) in the tube with a 5/8 drill bit or unibit. Be sure not to touch any wires inside the tube. File the edges of the hole.
5. Drill the upper and lower holes with the 9/64 drill bit provided.
6. Mount the mic to the mic plate with the 3/8 mic nut and washer provided.
7. Reconnect the mic to the mic harness.
8. Slide the mic wire into the 5/8 hole and secure the mic plate with the #8 x 1/2 Phillips flat screws provided.
9. Plug the old mic hole with the 3/8 hole plug provided.
10. Test the audio for proper operation.



